

MACHINE SPECIFICATIONS

*Specifications subject to change without notice.

MACHINE SPECIFICATIONS		
*Specifications subject to change without notice.		
	SW-3660 ELECTRIC HEAT	SW-3660 GAS HEAT
WORK CAPACITY		
HEIGHT	60"	60"
TURNTABLE DIA.	36"	36"
LOAD WEIGHT	2000 LBS	2000 LBS
FLOOR SPACE REQUIRED		
HEIGHT	110"	110"
WIDTH	69"	69"
WIDTH w/ OIL SKIMMER	81"	81"
LENGTH: DOOR OPEN	118"	118"
DOOR CLOSED	77"	77"
LOADING HEIGHT ABOVE FLOOR	32"	32"
SHIPPING WEIGHT	3000 LBS	3000 LBS
CLEANING SYSTEM		
SOLUTION CAPACITY	225 gals.	225 gals.
PUMP MOTOR	15 HP	15 HP
PUMP OUTPUT	80 psi @ 225 gpm	80 psi @ 225 gpm
SPRAY NOZZLES	27 alternating	27 alternating
FILTER SCREEN	2550 sq."	2550 sq."
CABINET CONSTRUCTION		
GAUGE STEEL	12 gauge	12 gauge
INSULATION	1" fiberglass	1" fiberglass
STEAM VENT	6"	6"
GAS VENT	6"	6"
HEAT SOURCE		
ELECTRIC ELEMENT	21.5W	N/A
GAS BURNER	N/A	180,000 BTU
HOT TANK BASKET		
WIDTH (I.D.)	24	24"
LENGTH (I.D.)	44"	44"
DEPTH (I.D.)	11"	11"
ELECTRICAL REQ.		
PUMP MOTOR 3 PHASE AMP DRAW	208/230/*460 Volts 38-34-17 Amps	
ELECTRICAL HEAT 3 PHASE AMP DRAW	208/230/460 Volts 60-52-26 Amps	N/A
STANDARD EQUIPMENT		
LOW WATER CUT OFF SWITCH	ELECTRIC HEAT ONLY	
DUAL 7 DAY TIMERS	STANDARD	
DIGITAL TEMP CONTROLLER	STANDARD	
HEAD RACK/CRANK RACK	STANDARD	
AUTO AIR INDUCER	STANDARD	
SHORT CIRCUIT/THERMAL PROTECTION	STANDARD	
LAY DOWN DOOR/SEALESS	STANDARD	
V-BOTTOM FLOOR	STANDARD	
BUILT IN HOT TANK	STANDARD	
MOISTURE PROOF ELECTRONICS	STANDARD/GAS MACHINES	
360 DEGREE MANIFOLD	STANDARD	
PNEUMATIC DOOR CLAMP	STANDARD	
WARRANTY	ONE YEAR	